

# Hz Acoustic Panel 025



## Areas of application

Hz acoustic panels can be glued to ceilings or walls that are fixed and solid, as well as suspended constructions of plaster or fibre concrete. Can be used in dry and wet areas. Supporting surfaces must be able to support a minimum of 10 kg/m<sup>2</sup>

## Material base

Basotect, Polymer foam on a melamine resin base

## Storage

Panels are stored free of frost and moisture. The temperature must not exceed 40 degrees Celsius and panels must not be stored in direct sunlight.

Place panels on site 2-3 days prior to start-up to moisture stabilise the panels.

## Execution

The surface must be even, dry, free of grease and loose substances. Loose plaster, chalking and other non-viable supporting surfaces are removed and the substrate is primed with Hz Plaster Primer. Previously painted as well as new surfaces must be primed with Hz Plaster Primer. Hz acoustic panels are fully glued with Hz glue, consumption 0.600 – 0.800 kg/m<sup>2</sup>. Read the supplier's instructions.

## Drying time

At 20 degrees Celsius and 50% RH, the adhesive is stable after 15-20 min and fully cured after 24 hours.

## Instructions

For information on safety during transport, storage, handling and disposal, see the Safety Data Sheet for the product. The above statements, including particular suggestions for the processing and use of our product, are based on our knowledge and experience in normal cases and assume that the products are stored and used correctly. Due to different materials, supporting surfaces and working conditions, no general guarantee can be given for the outcome or adhesion. It is the responsibility of the user of the products at all times to verify their suitability for the purpose.

# Hz Acoustic Panel 025



Hz ACOUSTIC

## Specifications

Panel thickness	40 mm
Panel format	1200 x 600 mm (0,72 m <sup>2</sup> )
Use	1,39 panels per m <sup>2</sup>
Colour	Light blue
Fire class	B-s1, d0 according to EN 13501-1

Sound test can be done on request

## Acoustic Plaster, that can be used for Hz Acoustic Panel 025



Hz Acoustic Plaster 03